

## SMS E300 Series

### DESCRIPTION

A high quality pressure sensitive vinyl suitable for signs on all flat surfaces, both interior and exterior use, with a medium term durability.

**Colors:** White and Yellow gloss, others on request

### TECNICAL INFORMATION

<b>Film</b>	Calendered P.V.C.
<b>Thickness film (without adhesive)</b>	75 +/- 5% micron
<b>Liner</b>	Clay coated paper 1 side siliconised
<b>Release</b>	70 +/- 20 cN/20 mm
<b>Adhesive</b>	Permanent eco-acrylic high cohesion
<b>Grammage</b>	25 +/- 5 g/m <sup>2</sup>
<b>Peel 180° after 20' on steel at 20°C (Istr. op. N° 7)</b>	min. 650 g/25 mm
<b>Peel 180° after 24 h on steel at 20°C (Istr. op. N° 7)</b>	min. 1150 g/25 mm
<b>Shrinkage (48 h at 70°C on steel)</b>	< 0,3 mm
<b>Life *</b>	3-4 years outdoor (When properly processed and under vertical condition)
<b>Application temperature</b>	Suggested between 10 and 28 °C
<b>Temperature resistance</b>	From -40°C to +80°C adhered to steel no variation
<b>Seawater resistance (Istr. op. N° 14)*</b>	Adhered to steel no variation after 100 h at 20°C (Ist. Op. 14)
<b>Shelf life</b>	2 years normal condition (20°C - 50% R.H.) suspended horizontally or vertically upright position in polytene bag.

\* References made to outdoor durability is based on middle european conditions. Exposure to conditions of high temperature as in southern climatic regions or in high polluted areas or in high altitudes or high UV conditions will reduce the performance levels. The values and data given are based on tests we believe to be reliable, and are typical values which are intended only as a source of information and do not constitute a warranty or a guarantee. The minimum life and seawater values given only refer to the film. Purchasers must independently determine, before use, the suitability of this material for the specific purpose and under their own operating conditions. No salesman, representative or agent has authority to give any guarantee, warranty or make any representation contrary to these guidelines. . guarantee, warranty or make any representation contrary to these guidelines .

Sheet n° : 6

Ed. : dic/03

Rev. : 2

**Bestel makkelijk en snel op [www.rebo.nl](http://www.rebo.nl)**

Op alle verkopen van onze producten zijn onze algemene leverings- en Betalingsvoorwaarden van toepassing, welke gedeponereerd zijn bij de kamer van koophandel Gooi- en Eemland onder nummer

**Rebo Belettering**  
**Dat is duidelijk!**

Postbank 35 51 626  
ING Bank 68 45 10 197  
IBAN nr.: NL38 INGB 0684 5101 97  
BIC nr.: INGBNL2A  
BTW/VAT NL8042 74 939 B01