

SMS ST700 series

DESCRIPTION

Pressure sensitive polymeric vinyl suitable for and flat and contoured surfaces.
The film is suitable for wet and dry applications.

Colors: 15 gloss

TECNICAL INFORMATION

Film	Industrial Calendered P.V.C.
Thickness film (without adhesive)	70 +/- 5% micron
Liner	Clay coated paper 1 side siliconised
Release	70 +/- 20 cN/20 mm
Adhesive	Ultra-Permanent acrylic
Grammage	25 +/- 5 g/m ²
Peel 180° after 20' on steel at 20°C (Istr. op. N° 7)	min. 1400 g/25 mm
Peel 180° after 24 h on steel at 20°C (Istr. op. N° 7)	min. 1800 g/25 mm
Shrinkage (48 h at 70°C on steel)	< 0,2 mm
Life *	8 years black and white, 7 years gloss colors (When properly processed and under vertical condition)
Application temperature	Suggested between 10 and 28 °C
Temperature resistance	From -40°C to +80°C adhered to steel no variation
Seawater resistance (Istr. op. N° 14)*	Adhered to steel no variation after 100 h at 20°C (Istr. Op. 14)
Shelf life	2 years normal condition (20°C - 50% R.H.) suspended horizontally or vertically upright position in polytene bag.

* References made to outdoor durability is based on middle european conditions. Exposure to conditions of high temperature as in southern climatic regions or in high polluted areas or in high altitudes or high UV conditions will reduce the performance levels. The values and data given are based on tests we believe to be reliable, and are typical values which are intended only as a source of information and do not constitute a warranty or a guarantee. The minimum life and seawater values given only refer to the film. Purchasers must independently determine, before use, the suitability of this material for the specific purpose and under their own operating conditions. No salesman, representative or agent has authority to give any guarantee, warranty or make any representation contrary to these guidelines. . guarantee, warranty or make any representation contrary to these guidelines .

Sheet n° : 15

Ed. : dic/03

Rev. : 1

Bestel makkelijk en snel op www.rebo.nl

Op alle verkopen van onze producten zijn onze algemene leverings- en Betalingsvoorwaarden van toepassing, welke gedeponereerd zijn bij de kamer van koophandel Gooi- en Eemland onder nummer

Rebo Belettering
Dat is duidelijk!

Postbank 35 51 626
ING Bank 68 45 10 197
IBAN nr.: NL38 INGB 0684 5101 97
BIC nr.: INGBNL2A
BTW/VAT NL8042 74 939 B01